

Message Delivery

Last Updated: Friday, January 26, 2018

The Message Delivery Services provide mechanisms to submit messages for delivery to a user as well as to query the status of previously submitted messages.

You can use the following methods to send or submit a message to either a single user, or to multiple users.

- *submitMtMessage* - A request to send a message to an individual Mobile Directory Number (MDN).
- *submitMtMessageList* - A request to send a message to several MDNs.

The *submitMtMessageList* is a convenience method that allows the same message to be sent to a small number of phone numbers, rather than making separate *submitMtMessage* calls. The messages will also be tagged with a *listId* for later identification that these messages were grouped.

Topics in this Section



Note - The *submitMtMessageList* is not a method for implementing Subscription Lists with a large number of Subscribers that regularly receive alert content.

Service	URI	Http Parameters	Comments
submitMtMessage	/MessageApi/mt/messages	POST:	Submits a new MT Message for delivery.
getMtMessage	/MessageApi/mt/messages/<messageId>	GET:	Retrieve the details on an MT Message.
getMtMessageResponses	/MessageApi/mt/messages/<messageId>/responses	GET:	Retrieve the MT Message responses for an MT message.
submitMtMessageList	/MessageApi/mt/messageLists	POST:	Submit a new MT Message list for delivery.
getMtMessageList	/MessageApi/mt/messageLists/<messageListId>	GET:	Retrieve the details on a Message list.