

# Person API Callback Events

Last Updated: Wednesday, November 17, 2021

The following methods describe how and why Person Added and Person Updated callback events are used, including examples.

## Person Added Callback

The Person Added callback event is triggered when a new Person record is added to your Mobile Database. The Person object represents the new state of the Person added.

### Callback Body



**Note:** MDN formats in callback events are determined by the API version used when creating and altering the callbacks. If Version 2 is used, MDNs will be represented in the [E.164](#) international format. Otherwise, MDNs will be represented without a country code.

```
{
  "event_id": "AB234SDFD234",
  "callback_type": "person_added",
  "event_type": "person_added", //deprecated
  "event_date": "2017-03-15T15:42:23Z",
  "person": {
    "person_id": "12344566",
    "external_person_id": "542342",
    "mobile_phone": {
      "mdn": "+12995551234",
      "carrier_code": "104"
    },
    "timezone": "US/Central",
    "timezone_source": "area_code",
    "custom_fields": {
      "first_name": "Steve",
      "birthdate": "1950-12-01T00:00:00Z",
      "rewards_id": "543557654",
      "favorite_stores": [
        {
          "id": "4",
          "name": "My Hardware Store",
          "option_key": "my_hardware_store"
        },
        {
          "id": "12",
          "name": "Local Grocery",
          "option_key": "local_grocery"
        }
      ]
    }
  },
  "created_at": "2017-01-15T14:30Z",
  "updated_at": "2017-02-18T19:30Z",
  "url": "/companies/:company_key/mobiledb/persons/:person_id"
}
```

## Person Updated Callback

The Person Updated callback event is triggered when an existing Person record has been modified in your Mobile Database. This includes scenarios where a Person was requested to be added, but an existing Person was located and matched because they already interacted with the platform (either by MDN or *external\_person\_id*).

The Person object represents the complete updated state of the Person.

### Callback Body



**Note:** MDN formats in callback events are determined by the API version used when creating and altering the callbacks. If Version 2 is used, MDNs will be represented in the [E.164](#) international format. Otherwise, MDNs will be represented without a country code.

```
{
  "event_id": "AB234SDFD234",
  "callback_type": "person_updated",
  "event_type": "person_updated", //deprecated
  "event_date": "2017-03-15T15:42:23Z",
  "person": {
    "person_id": "12344566",
    "external_person_id": "542342",
    "mobile_phone": {
      "mdn": "+12995551234",
      "carrier_code": "104"
    },
    "timezone": "US/Central",
    "timezone_source": "area_code",
    "custom_fields": {
      "first_name": "Steve",
      "birthdate": "1950-12-01T00:00:00Z",
      "rewards_id": "543557654",
      "favorite_stores": [
        {
          "id": "4",
          "name": "My Hardware Store"
        },
        {
          "id": "12",
          "name": "Local Grocery",
          "option_key": "local_grocery"
        }
      ]
    }
  },
  "created_at": "2017-01-15T14:30Z",
  "updated_at": "2017-02-18T19:30Z",
  "url": "/companies/:company_key/mobiledb/persons/:person_id"
}
```

## Additional Resources

- For information on how to register your endpoint to receive callbacks, see [Callback Configuration](#)
- [Client Certificate Authentication for Callbacks from the Vibes Platform](#)